



Don't open your *door* to the unknown



MDUV4-LX-VC (MDUV4-LX-Audio Only)

TeleDoorBell MDU Series

The TeleDoorBell MDU series is a full featured multi dwelling unit door entry intercom. This easy to install multi-tenant version can quickly connect up to 4 suites sharing a single entry point. Available with removable back box the MDUV4LX can be recessed or surface mounted. Your tenants are now connected through their phones to the TeleDoorBell MDU series door entry station without the need of running more cable to each suite or having your installing a costly line at the entry point. The MDUV4LX is available with or without 24/7 live video. Rugged, vandal resistant, the metal face plate will stand up against the elements for years. Perfect for commercial or residential applications, TeleDoorBell will seamlessly integrate to virtually any analogue, VOIP or business phone systems that may be on site.

Features

Call Forwarding: TeleDoorBell includes call forwarding that can instantly connect the front door station to your tenant's cell phone or secondary location without visitors ever knowing.

Relay Control: Built-in relays allows tenants to operate electronic door entry hardware such as strikes or bolts, magnetic locks, garage and bay doors from their phone or cell phone. garage and bay doors from any phone. Activate lighting, thermostat, alarm system and more instantly by pressing a few keys on your premise or cell phone.

Colour Video CCTV Camera: TeleDoorBell MDU video door stations feature high-resolution CCD cameras including infrared illuminators for clear images even in total darkness. Providing true 24/7 live video surveillance images TeleDoorBell video door stations are suitable for integration with DVRs, PCs, security monitors or televisions.

Call Waiting: When tenants are on another call, TeleDoorBell will sound a call waiting tone so they can place the call on hold, speak to the visitor then return back to their call. This feature works even if they don't subscribe to Call Waiting. For tenants without land line service, see the Logenex TBG2 module.

Caller ID/Distinctive Ring: Distinctive ring and caller ID identifies who is calling as every TeleDoorBell system features both Caller ID and distinctive ring.

Specifications

Audio (ADMDUV4 /ADMDUV4VC)

Power source	24VDC from controller
Current Draw	10mA
Distance to controller (24 AWG UTP)	1000'
Speaker type	2" 45ohm 0.5 watt
Volume control	Adjustable
Connection type	Terminal
Operation temperature	-20° to 50° C
Overall dimensions:	
Surface	8.56"(H) x 5.13"(W) x 2.1"(D)
Flush	8.56"(H) x 5.13"(W) x 1.65"(D)

Video (ADMDUV4VC Only)

Power source	250mA - 12VDC
Current Draw	185 mA
Distance to controller (24 AWG UTP)	250' video signal + 250' video power
Connection type	Terminal
Chip set	Sony SuperHAD
Resolution	580TVL High Resolution
F stop	1.2
Lux rating	0.01 lux
Infrared Throw	20'
S/N Ratio	>48db
Overall dimensions:	
Surface	8.56"(H) x 5.13"(W) x 2.1"(D)
Flush	8.56"(H) x 5.13"(W) x 1.65"(D)
Additional Features:	3D-DNR & SENSE-UP SS-WDR Color Calibration

6A-7500 Martin Grove Rd. Woodbridge, ON. Canada L4L 8S9
Toll Free: 1.888.790.5900 E-mail: info@logenex.com
For complete information please visit our website at www.logenex.com

AUTHORIZED DEALER