



Don't open your *door* to the unknown



C304CR

C Series Controller

At the heart of every TeleDoorBell system is the controller. The controller links your door stations to the phone system through its CA38A/RJ31X phone jack. Inside the controller resides the logic and hardware to carry out the functions of a TeleDoorBell system including the much talked about call forwarding feature that can connect you no matter where you are... instantly...without your visitors ever knowing you may not be on site.

When coupled with the Page/Mute module our HIFI series is capable of sending mute commands to your home audio distribution system for incoming phone calls and/or visitors. It also gives you the ability to page through your home audio speakers with any corded or cordless phone.

Features

All inclusive: TeleDoorBell controllers include everything you need to install a complete system in minutes, simply choose your TeleDoorBell door station and you are ready to install.

Approvals: TeleDoorBell controllers are UL/ULC approved and CSA approved for installations that require the highest standard.

Self contained: TeleDoorBell controllers have everything built-in including up to 4 fully configurable relays, timers, call waiting module, call forward module, door chime module, remote dial up module and distinctive rings for each door station with caller ID.

Easy to install: Simply connect 2 wires of almost any gauge from the door station to the controller, connect then CA38A/RJ31X jack and cord to the phone line, plug in the transformer and you're live.

Any phone system: TeleDoorBell can connect to any analogue or business phone system including VOIP phone systems.

Specifications

Number Of Doors:

C304CR 4 (max.)
C303HIFI 3 (max.)

Call Forward:

C304CR/C303HIFI Instant, Delay

Distinctive Ring Yes

Caller ID:

C304CR/C303HIFI Yes

**Audio Monitor/
Listen In** Yes

Number of ring attempts:

C304CR/C303HIFI 1 to 6 (selectable)

Remote dial up access:

C304CR/C303HIFI Yes (PIN required)

Relays: (2A-30VAC/DC)

C304CR 4 Momentary
(0.5s to 98s) /Latching 3
C303HIFI Momentary
(0.5s to 98s) /Latching

Relay door connection:

C304CR/C303HIFI Terminal Strip

Current draw 300mA

Ring output voltage 180V RMS without load/
140V with load

RJ31X/CA38A jack:

C304CR/C303HIFI 1 Included

Power supply 16VAC 500mA
(plug in type)

Operating temperature -20° to 50° C

Dimensions – Weight 1.8"(H) x 6.8"(W)
x 6.8"(L) – 1.15lbs.

19 Kenview Blvd. Unit 31, Brampton, ON. CAN. L6T 5G6

Toll Free: 1.888.790.5900 E-mail: info@logenex.com

For complete information please visit our website at www.logenex.com

AUTHORIZED DEALER